











Sistem  
**DIMOVODNE ZAKLOPKE**

MOTORNE DIMOVODNE ZAKLOPKE		
motorna dimovodna zaklopka za sisteme dimovoda u podtlaku, prikladno kao zaporni uređaj	motorna dimovodna zaklopka, obostrano sa priрубnicom prema tvorničkoj normi tvrtke Jeremias, materijal 1.4404, tlačno nepropusna do 5000 Pa, motor 40 Nm, brzina zatvaranja 150 s	motorna dimovodna zaklopka sa priрубnicom za režim rada u podtlaku, prikladna za velike kotlove kao zaklopa za uštedu energije
		
<b>MAK</b>	<b>MAKHPGM</b>	<b>MAKV</b>

MOTORNE DIMOVODNE ZAKLOPKE	RUČNE DIMOVODNE ZAKLOPKE	
motorna dimovodna zaklopka, obostrano s priрубnicom prema tvorničkoj normi tvrtke Jeremias, materijal 1.4404, vratilo toplinski odvojeno i tlačno nepropusno do 5000 Pa, motor 90 Nm, brzina zatvaranja 17 s	motorna dimovodna zaklopka, obostrano s priрубnicom prema tvorničkoj normi tvrtke Jeremias, materijal 1.4404, vratilo toplinski odvojeno i tlačno nepropusno do 5000 Pa, motor 20 Nm, brzina zatvaranja 20 s	motorna dimovodna zaklopka za manualno podešavanje, obostrano s priрубnicom prema tvorničkoj normi tvrtke Jeremias, materijal 1.4404, vratilo toplinski odvojeno i tlačno nepropusno do 5000 Pa
		
<b>MAKHTSY</b>	<b>MAKHTSF</b>	<b>AKHT</b>

POKLOPCI ZA IZJEDNAČAVANJE TLAKA		
Joukowski poklopac za izbjegavanje udara podtlaka (bez T-dijela)	Joukowski poklopac za izbjegavanje udara podtlaka (s priključkom T-dijela 45°)	poklopac za rasterećenje tlaka
		 <span style="color: red; font-weight: bold;">NOVO</span>
<b>ZUTE1104-1</b>	<b>ZUTE1104</b>	<b>ZUTE-1630</b>